



**Medtronic**  
PHYSIO-CONTROL

# LIFEPAK® 12

Defibrillator / Monitor Series

Small, lightweight, rugged unit provides therapy and multi-parameter monitoring

Simple operation, dedicated therapy controls and one-touch operation

Configurable options and convenient field upgrades

Automated External Defibrillator (AED) capability with Shock Advisory System™

Extensive data storage, transmission and retrieval capabilities

LIFENET® system compatible

## OPTIONS:

ADAPTIV™ Biphasic or monophasic defibrillation waveforms

EL or LCD display

Noninvasive pacing

GE Medical 12SL® ECG analysis program

Nellcor™ pulse oximetry (SpO<sub>2</sub>)

Microstream™ Capnography (EtCO<sub>2</sub>)

Invasive Pressures (2)

Vital signs trending

AC or DC Power Adapter

NiCd or SLA batteries



Medtronic Physio-Control offers leading edge solutions for the problems you face today and configurable capabilities for the solutions you will need tomorrow. The LIFEPAK 12 defibrillator/monitor series provides therapeutic and diagnostic functions in a single, small device designed for both out-of-hospital and hospital users. The innovative platform design provides full-featured defibrillation and industry-standard monitoring all loaded into a single portable device.

The 12 offers a choice of ADAPTIV Biphasic or industry standard monophasic (Edmark) defibrillation waveforms, with the capability to deliver shocks at energy levels recommended by the American Heart Association in collaboration with the International Liaison Committee on Resuscitation (ILCOR). Both

monophasic and biphasic devices utilize the same field-proven Shock Advisory System used in thousands of LIFEPAK AEDs since 1986.

Configurable options, including AED and manual defibrillation modes, allow standardization across user groups and ease of patient transfer.

Dedicated defibrillation and pacing therapy buttons provide fast and effective therapy for both beginning and advanced users. The Selector knob and home screen button make it simple to switch between menus.

In AED mode, the LIFEPAK 12 defibrillator/monitor series utilizes the Medtronic Physio-Control field proven Shock Advisory System with clear, voice prompts to advise



**GENERAL**

The LIFEPAK 12 defibrillator/monitor series has five main operating modes:

**Advisory Mode (SAS):** Provides all features available except manual defibrillation, synchronous cardioversion and pacing.

**Manual Mode:** Provides normal operating capability for ALS users.

**Setup Mode:** Allows operator to customize the device.

**Service Mode:** Allows operator to execute device diagnostic tests and calibrations.

**Inservice Mode:** Provides simulated waveforms for demonstration purposes.

**POWER**

**Battery Only Configuration:** Choice of NiCd (FASTPAK® battery, FASTPAK 2 battery, LIFEPAK NiCd battery) or SLA (LIFEPAK SLA battery)

Dual battery capability

Optional external AC and (+12) VDC Power Adapters

Batteries charge while device operates from Power Adapter

**Operating Time:** Two new fully charged batteries will provide the following prior to shutdown:

	TOTAL				AFTER LOW BATTERY			
	Typical		Min.		Typical		Min.	
	LCD	EL	LCD	EL	LCD	EL	LCD	EL
Monitoring (minutes)								
NiCd*	110	81	60	43	10	6	2	1
NiCd**	155	114	85	62	14	8	2	1
NiCd***	220	162	120	86	20	12	4	2
SLA	180	132	100	73	16	10	2	1
Defibrillation (360 joule discharges)								
NiCd*	80	72	45	40	7	7	3	3
NiCd**	110	99	60	54	10	10	3	3
NiCd***	160	144	90	80	14	14	6	6
SLA	145	131	85	76	12	12	3	3
Monitoring plus pacing (minutes at 100ma, 60ppm)								
NiCd*	105	75	60	42	9	6	2	1
NiCd**	145	104	85	60	12	8	2	1
NiCd***	210	150	120	84	18	12	4	2
SLA	170	122	100	71	14	10	2	1

Monitoring (minutes)

NiCd*	110	81	60	43	10	6	2	1
NiCd**	155	114	85	62	14	8	2	1
NiCd***	220	162	120	86	20	12	4	2
SLA	180	132	100	73	16	10	2	1

Defibrillation

(360 joule discharges)

NiCd*	80	72	45	40	7	7	3	3
NiCd**	110	99	60	54	10	10	3	3
NiCd***	160	144	90	80	14	14	6	6
SLA	145	131	85	76	12	12	3	3

Monitoring plus pacing

(minutes at 100ma, 60ppm)

NiCd*	105	75	60	42	9	6	2	1
NiCd**	145	104	85	60	12	8	2	1
NiCd***	210	150	120	84	18	12	4	2
SLA	170	122	100	71	14	10	2	1

\*FASTPAK, FASTPAK 2

\*\*LIFEPAK NiCd 3009376-00

\*\*\*LIFEPAK NiCd 3009376-01

**Low Battery Indication and Message:** Low battery icon at top of display and low battery message in status area for each battery. When low battery is indicated, device autoswitches to second battery. When both batteries reach a low battery condition, there is a voice prompt to replace battery.

**Warmstart:** With inadvertent loss of power (<30 seconds) device retains settings.

**Service Indicator:** When error detected

**PHYSICAL CHARACTERISTICS**

**Weight:** Basic defibrillator/monitor with QUIK-COMBO™ cable: 6.0kg (13.3 lbs) (unit and QUIK-COMBO cable only, no batteries)

**FASTPAK and FASTPAK 2 battery:** .6kg (1.3 lbs)

**LIFEPAK NiCd battery:** 0.8kg (1.7 lbs)

**LIFEPAK SLA battery:** 1.3kg (2.8 lbs)

**Standard paddles (hard):** 0.9kg (1.9 lbs)

**Height:** 31.7cm (12.5 in)

**Width:** 38.9cm (15.3 in)

**Depth:** 21.7cm (8.5 in)

**DISPLAY**

**Size (active viewing area):**

**LCD:** 140.8mm (5.5 in) wide x 105.6mm (4.2 in) high

**EL:** 165.1mm (6.5 in) wide x 123.8mm (4.9 in) high

**Resolution:**

640 x 480 black and white LCD

640 x 480 amber and black EL display

User selectable LCD contrast

Displays a minimum of 4 seconds of ECG and alphanumeric for values, device instructions or prompts.

Option to display one or two additional waveforms

**Waveform display sweep speed:** 25mm/sec for ECG and 12.5mm/sec of CO<sub>2</sub>

**DATA MANAGEMENT**

The device captures and stores patient data, events (including waveforms and annotations), user test results and continuous ECG waveform records in internal memory.

The user can select and print reports and transfer the stored information via an internal modem through landline or mobile phones.

**Report Types:** Three format types of CODE SUMMARY™ critical event record (short, medium and long)

- Initial ECG (except short format)
- Automatic capture of vital signs measurements every 5 minutes
- 3-channel or 4-channel 12-lead ECG report
- Continuous waveform records (transfer only)
- Trend Summary – includes patient information, vital signs log and vital signs graphs
- Vital Signs – includes patient information, event and vital signs log.
- Snapshot – includes patient information and 8 seconds of ECG captured at the time of transmission

**Memory Capacity:**

**Two full-capacity patient records that include:**

CODE SUMMARY critical event record – up to 100 single waveform events

Continuous Waveform – 45-minute continuous ECG record

**COMMUNICATIONS**

The device is capable of transferring data records by internal modem, external EIA/TIA modem, cellular modem or serial connection.

Supports EIA/TIA-602 compatible modems using Xon/Xoff or RTS/CTS flow control at 9600 to 38400 bps.

EIA/TIA-RS232E compatible at 9600, 19200, 38400 and 57600 bps.

Group III, Class 2 or 2.0 fax

**MONITOR**

**Voice Prompts:** Used for selected warnings and alarms (configurable on/off).

**ECG**

**ECG is monitored via several cable arrangements.**

A 3-wire cable is used for 3-lead ECG monitoring.

A 5-wire cable is used for 7-lead monitoring.

A 10-wire cable is used for 12-lead acquisition. When the chest electrodes are removed, the 10-wire cable functions as a 4-wire cable.

Standard paddles or QUIK-COMBO pacing/defibrillation/ECG electrodes or FAST-PATCH® disposable defibrillation/ECG electrodes are used for paddles lead monitoring.

**Lead Selection:** Leads I, II, III, (3-wire ECG cable)

Leads I, II, III, AVR, AVL and AVF acquired simultaneously (4-wire ECG cable)

Leads I, II, III, AVR, AVL, AVF, V1 (Labeled "C" on 5-wire ECG cable)

Leads I, II, III, AVR, AVL, AVF, V1, V2, V3, V4, V5 and V6 acquired simultaneously, (10-wire ECG cable)

**ECG Size:** 4, 3, 2.5, 2, 1.5, 1, 0.5, 0.25 cm/mV (fixed at 1 cm/mV for 12-lead)

**Heart Rate Display:** 20 to 300 bpm digital display

**Out of range indication:** Display symbol "—"

Heart symbol flashes for each QRS detection

**Continuous Patient Surveillance System (CPSS):** In advisory mode while Shock Advisory System is not active, CPSS monitors the patient, via paddles or Lead II ECG, for potentially shockable rhythms.

**Analog ECG output:** 1V/mV x 1.0 gain

**Common Mode Rejection:** 90dB at 50/60Hz

**SpO<sub>2</sub>**

**Nellcor sensors**

**SpO<sub>2</sub> Measurement Range:** 50 to 100%

**SpO<sub>2</sub> Waveform:** IR pleth signal

**SpO<sub>2</sub> Update Rate:** as each pulse is detected

**Calibration Range:** 70 to 100%

**SpO<sub>2</sub> Measurement:** Functional SpO<sub>2</sub> values are displayed and stored

**Pulse Rate:** +/- 3 pulses per minute

Dynamic signal strength bar graph

Pulse tone proportional to value of displayed oxygen saturation

**NIBP**

**Oscillometric measurement**

**Systolic Pressure Range:** 30 to 245mmHg

**Diastolic Pressure Range:** 12 to 210mmHg

**Units:** mmHg, kPa

**Mean Arterial Pressure Range:** 20 to 225mmHg

**Blood Pressure Accuracy:** maximum mean error of ± 5mmHg with a standard deviation no greater than ± 8mmHg

**Pulse Rate Range:** 30 to 200 pulses per minute

**Pulse Rate Accuracy:** ± 2 pulses per minute or ± 2% whichever is greater

**Typical Measurement Time:** 40 secs

## EtCO<sub>2</sub>

### Microstream™ technology

**Measurement Range:** 0 to 99mmHg

**Display:** CO<sub>2</sub> waveform and EtCO<sub>2</sub> numerics

**Units:** mmHg, kPa, %; user selectable

Automatic ambient pressure compensation

**CO<sub>2</sub> Accuracy (>20 minutes):** 0 to 38mmHg: ± 2mmHg  
39 to 99mmHg: ± 5% of reading + 0.08% for every 1mmHg

**Warm Up Time:** 30 seconds (typical), 180 seconds max

**Response Time:** 2.9 seconds (includes delay time and rise time)

**Respiration Rate Range:** 0 to 60 breaths per minute

**Respiration Rate Accuracy:** 0 to 40 bpm: ± 1 bpm  
41 to 60 bpm: ± 2 bpm

### Invasive Pressure (2 channels)

**Measurement range:** -30 to +300mmHg in six user selectable ranges

**Display:** IP waveform and numerics

**Units:** mmHg, kPa

**User-selectable labels:** ART, PA, CVP, ICP, LAP

**Transducer type:** Strain-gauge resistive bridge

**Transducer sensitivity:** 5mV/V/mmHg

**Bandwidth:** 0 - 30 Hz (<3dB)

**Numeric accuracy:** ± 1mmHg or 2% of reading, whichever is greater, plus transducer error

**Leakage current:** Meets ANSI/AAMI/IEC requirements

### Trend

**Display:** Choice of HR, SpO<sub>2</sub>(%), EtCO<sub>2</sub>, RR, NIBP, P1, P2, ST shown in channels 2 or 3.

**Time scale:** Auto, 30 minutes, 1, 2, 4 or 8 hours

**Duration:** Up to 8 hours with -06 Memory PCB or later. Reduced storage capacity with earlier versions.

**ST segment:** After initial 12-lead ECG analysis, automatically selects and trends lead with the greatest ST displacement.

## ALARMS

**Quick Set:** Activates alarms for all parameters.

**VF/VT Alarm:** Activates continuous CPSS monitoring in Manual Mode.

**Apnea alarm:** Occurs when 30 seconds have elapsed since last detected respiration.

## INTERPRETIVE ALGORITHMS

**12-lead Interpretive algorithm:** GE Medical 12SL, Includes AMI statements.

## PRINTER

**Prints continuous strip of the displayed patient information**

**Paper Size:** 50mm (2.0 in) or optional 100mm (3.9 in)

**Print Speed:** 25mm/Sec +/- 5% (measured in accordance with AAMI EC-11, 4.2.5.2)

**Delay:** 8 seconds

**Autoprint:** Waveform events print automatically (user configurable)

Optional 50mm/sec timebase for 12-lead ECG reports

## FREQUENCY RESPONSE

**Diagnostic:** 0.05 to 150Hz or 0.05 to 40Hz (user configurable)

**Monitor:** 0.67 to 40Hz or 1 to 30Hz (user configurable)

**Paddles:** 2.5 to 30Hz

**Analog ECG Output:** 0.67 to 32Hz (except 2.5 to 30Hz for Paddles ECG and 1.3 to 23Hz for 1 to 30Hz monitor frequency response)

## DEFIBRILLATOR

**Waveform (Biphasic):** Biphasic truncated exponential with voltage and duration compensation for patient impedance.

**Waveform (Monophasic, Edmark):** Damped sinusoid in shape per AAMI DF2-1989, 3.2.1.5.1

**Energy accuracy:** ±1 joule or 10% of setting, whichever is greater, into 50 ohms.

±1 joule or ±5%, whichever is greater, of 50 ohm value into 25 to 200 ohms.\*

**Paddle Options:** QUIK-COMBO pacing/defibrillation/ECG electrodes (standard)

FAST-PATCH disposable defibrillation/ECG electrodes (optional)

Standard Paddles (optional)

Internal Handles with discharge control (optional)

External Sterilizable Paddles (optional)

**Cable Length:** 2.4m (8 ft) long QUIK-COMBO cable (not including electrode assembly)

## MANUAL

**Energy Select (Monophasic):** 2, 3, 4, 5, 6, 7, 8, 9, 10, 20, 30, 50, 70, 100, 150, 200, 300 and 360 joules or user configurable sequence 200/200/360 or 200/300/360 joules

**Energy Select (Biphasic):** 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 20, 30, 50, 70, 100, 125, 150, 175, 200, 225, 250, 275, 300, 325, and 360 joules or user configurable sequence 100 to 200, 100 to 300, 100 to 360.

**Charge Time:** Charge time to 360J in less than 10 seconds, typical

**Synchronous Cardioversion:** Energy transfer begins within 60mS of the QRS peak

## ADVISORY

**Shock Advisory System (SAS) is an ECG analysis system that advises the operator if the algorithm detects a shockable or non-shockable ECG rhythm. SAS acquires ECG via therapy electrodes only.**

**Shock Ready Time:** Using a fully charged battery at normal room temperature, the device is ready to shock within 20 seconds if the initial rhythm finding is "Shock Advised."

**Output Energy (Edmark):** User configurable, sequence of 200/200/360 or 200/300/360 joules.

**Output Energy (Biphasic):** User configurable, sequence of three sequential shock levels ranging from 200, 200 to 300, and 200 to 360 joules.

\* Note: ±5% accuracy applies when disposable therapy electrodes are attached. Energy output is limited to the available energy which results in delivery of 360 joules into 50 ohms.

## PACER

**Pacing Mode:** Demand or non-demand  
Rate and current defaults (user configurable)

**Pacing Rate:** 40 to 170ppm

**Rate Accuracy:** +/- 1.5% over entire range

**Output Waveform:** Monophasic, truncated exponential current pulse (20 + 1ms)

**Output Current:** 0 to 200mA

**Pause:** Pacing pulse frequency reduced by a factor of 4 when activated

**Refractory Period:** 200 to 300mS +/-3% (function of rate)

## ENVIRONMENTAL

**Temperature, Operating:** 0° to 50°C (32° to 122°F)  
SpO<sub>2</sub>: 5° to 45°C (41° to 113°F)

**Temperature, Non-operating:** -20° to +60°C (-4° to 140°F) except therapy electrodes and batteries

**Relative Humidity, Operating:** 5 to 95%, non-condensing

**Atmospheric Pressure, Operating:** Ambient to 429mmHg (0 to 4572m) (0 to 15,000 ft)

**Water Resistance, Operating:** IPX4 (splash proof) per IEC 529 (with batteries and cables installed)

**EMC: Emissions:** MIL-STD-461D, RE101; EN55011, class B, Group 1

**Susceptibility:** MIL-STD-461D, CS114, RS101

**Shock (drop):** Five drops on each side from 18 in. onto a steel surface

**Vibration:** MIL-STD-810E Method 514.4, Propeller Aircraft – category 4, Helicopter – category 6 (3.75g), and Ground Mobile – category 8 (3.14g)

## AC AND DC POWER ADAPTER

### Function

**Dimensions:** 27.7 x 16.8cm (10.9 x 6.6 in)

**Weight:** < 2.3kg (<5 lbs) (including cables)

**Charge Time (with fully depleted battery):** FASTPAK and FASTPAK 2: 1.5 hours

LIFEPAK NiCd 3009376-00: 2.1 hours

LIFEPAK NiCd 3009376-01: 3.0 hours

LIFEPAK SLA: 6 hours typical, 12 hours maximum

**AC Input:** Accepts line power from both: 90 to 264VAC, 47 to 63Hz (domestic/international) 108 to 118VAC, 380 to 420Hz (military)

**DC Input:** 9 to 16VDC

**Fuses:** Two 250V fuses (100 to 200V: T5A; 220 to 240V: T2.5A) in the power input module (AC Power Adapter only)

### Environmental

**IPX4 per IEC 529**

**Altitude, Operating:** To 4545m (15,000 ft)

**Altitude, Non-operating:** To 5455m (18,000 ft)

**Humidity:** 5 to 95% non-condensing

**Temperature, Operating:** 0° to 50°C (32° to 122°F)

**Temperature, Storage:** -20° to 65°C (-4° to 150°F) (followed by one hour temperature stabilization in operating temperature range)

**Vibration, Operating and Non-operating:** MIL-STD-810E, Method 514.4 Categories 4, 6, 8

All specifications are at 20°C unless otherwise stated.

◀ operator when it detects a shockable rhythm with visual and voice prompts. In manual mode, the LIFEPAK 12 defibrillator/monitor series features simple 1-2-3 operation.

Large display allows 1, 2 or 3 ECG channels to be viewed simultaneously, with up to eight seconds of cascading ECG. Heart rate, oxygen saturation and other vital information is clearly visible.

GE Medical's 12SL ECG analysis program offers interpretive 12-lead ECG analysis. The 12SL ECG analysis program provides accuracy with simultaneous acquisition, analysis and interpretation of all 12-leads. 12-lead transmission capabilities give you a head start in diagnosis and treatment of AMI and other conditions. Patient data, including 12-lead ECG reports can be integrated into the GE Medical MUSE CV® cardiovascular information system.

Pulse oximetry is available with Nellcor C-LOCK ECG synchronization for timing pulse oximetry measurements with ECG signal.

Capnography (EtCO<sub>2</sub>) monitoring is available for use on intubated and nonintubated patients. Superior moisture handling eliminates the need for water traps or additional moisture filters. Innovative Microstream™ technology and FilterLine™ accessories reduces maintenance costs associated with mainstream sensor and cable damage.

Oscillometric noninvasive blood pressure (NIBP) monitoring with proven performance in most ambient noise and motion environments is also available. Automatic measurement modes provide vital sign assessment at intervals appropriate for patient condition.

The AC and DC Power Adapters provide line power as well as battery charging capability. A full line of batteries are available to meet varied usage requirements, with fuel gauge indicators providing visual indication of remaining capacity.