



FEATURES AND BENEFITS

- Flexible stretcher design with 26" or 29" patient surface can be configured to best suit your department's needs
- Steel-ring brakes with optional four-sided brake controls ensure a firmly-locked working surface
- Optional, accessible four-sided brake controls (not available with BIG WHEEL® option)
- Standard locking caster steering for better traction and cornering (fifth-wheel or BIG WHEEL option also available)

COLOR OPTIONS



THE BIG WHEEL OPTION INCREASES YOUR MOBILITY AND DECREASES YOUR PUSHING EFFORT

ADVANTAGE™ STRETCHERS

STANDARD FEATURES

- 3" (8 cm) mattress
- 8" (20 cm) Omni Surface™ casters
- 26" (66 cm) or 29" (73 cm) wide patient surface
- Dual pedestal hydraulics
- Dual side-mounted foot control hydraulics
- Fibersin backrest/steel foot-end litter
- Fold-down siderails (models 1009, 1509 only)
- Glideaway™ siderails (models 1001, 1501 only)
- Four IV receptacles
- Four-wheel, steel-ring ring brakes with dual end activators
- Integrated storage tray with oxygen bottle holder
- Locking caster steering
- Rubber bumpers
- Unilower pedal

OPTIONAL FEATURES

- BIG WHEEL®
- 3" (8 cm) or 4" (10 cm) Enhanced Comfort Mattress
- 4" (10 cm) or 5" (13 cm) Ultra Comfort Mattress
- 4" (10 cm) mattress
- Crank backrest
- Crank knee gatch
- Constant descent hydraulics
- Defibrillator tray
- Defibrillator tray/extender/footboard
- Dual end-mounted foot control hydraulics
- Dual end siderail latch (models 1001, 1501 only)
- Dual lowering pedals
- Fold- or glide-to-foot siderails
- Footboard
- Footboard/chartholder
- Four-sided brake & steer pedals
- Backrest x-ray cassette holder
- Heel stirrups
- IV caddy
- Lateral C-spine cassette film holder
- Patient restraints
- Pop-up push handles
- Push bar/headboard/writing surface (models 1001, 1501 only)
- Removable push bar
- Retractable fifth-wheel steering
- Serving/instrument tray
- Siderail pads
- Upright oxygen bottle holder
- Wheel covers
- IV poles
 - permanent folding two- or three-stage Infusion™ II
 - tethered
 - standard removable
- Extended warranty available

SPECIFICATIONS

• Model Numbers	1001	1009	1501	1509
• Overall Length	83" (211 cm)	84" (213 cm)	83" (211 cm)	84" (213 cm)
• Overall Width				
<i>Siderails Up</i>	31.5" (80 cm)	31.5" (80 cm)	34.5" (88 cm)	34.5" (88 cm)
<i>Siderails Down</i>	30" (76 cm)	31.5" (81 cm)	30.5" (78 cm)	34.5" (88 cm)
• Weight Capacity	500 lb (228 kg)	500 lb (228 kg)	500 lb (228 kg)	500 lb (228 kg)
• Height Range (to litter top)				
<i>High</i>	35.5" (90 cm)	35.5" (90 cm)	35.5" (90 cm)	35.5" (90 cm)
<i>Low</i>	22" (56 cm)	22" (56 cm)	22" (56 cm)	22" (56 cm)
• Litter Positioning				
<i>Backrest</i>	0° - 90°	0° - 90°	0° - 90°	0° - 90°
<i>Knee Gatch</i>	0° - 30°	0° - 30°	0° - 30°	0° - 30°
<i>Trend./reverse Trend.</i>	±18°	±18°	±18°	±18°
• Patient Surface	26" x 76"	26" x 76"	29" x 76"	29" x 76"
	(66 x 193 cm)	(66 x 193 cm)	(74 x 193 cm)	(74 x 193 cm)
• Siderails	14" x 54"	13" x 55"	14" x 54"	13" x 55"
	(36 x 137 cm)	(33 x 140 cm)	(36 x 137 cm)	(33 x 140 cm)
• Caster Diameter	8" (20 cm)	8" (20 cm)	8" (20 cm)	8" (20 cm)

LABEL OPTIONS

Ambulatory Surgery	Maternity	Cath Lab	Nuclear Medicine
Emergency	PACU	Extended Stay	Radiology
Surgery	Trauma	Cardiology	Transport
Same Day Surgery	UltraSound	GI Lab	Outpatient Surgery
Recovery	Endoscopy		

Stryker reserves the right to change specifications without notice.



stryker
Medical

Stryker Medical is ISO 9001 certified