

Valueklave 1730

The Speed and Quality you Demand
with the Value you Deserve



tuttnauer

Sterilization & Infection Control Products

The Valueklave 1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave 1730



Valueklave 1730 Specifications

Chamber Dimensions Ø x L In (mm)	6.7"x13.4" (170 x 340)
Volume	2gal/7.5L
Overall Dimensions DxWxH In (mm)	17.9"x17.4"x12" (455 x 440 x 305)
Standard Cassettes	2 half
Tray Dimensions DxWxH In (mm)	4.7"x11.6"x 0.8" (120 x 295 x 20)
No. of Trays	3
Standard Unwrapped Cycle Time	Cold: 12 mins Hot: 9 mins
Voltage (V)	120 / 230
Freq. (Hz)	60 / 50
Power (W)	1350W
Current (A)	11A
Shipping Weight lbs (kg)	55 (25)

Features:

- Fast Cycle Time. 9 minutes from a hot start* (Standard Unwrapped Cycle time).
- Automatic shut off at the end of both the sterilization and dry cycles
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Overheat cutoff prevents burnout of heating elements in case of insufficient water in the chamber.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.



Chamber Brite™

One of the most effective and easy to use autoclave cleaners. Chamber Brite effectively cleans and descales the chamber, reservoir, and copper tubing of most steam autoclaves. Available 10 per box. Item No. CB0010.



tuttnauer
Sterilization & Infection Control Products